# PRODUCT DATA SHEET

# Purolite® A845DL

Polyacrylic Gel, Weak Base Anion Resin, Free Base form, Layered Bed grade

## PRINCIPAL APPLICATIONS

• Demineralization - High organics water

## **ADVANTAGES**

- Excellent chemical and thermal stability
- Excellent resistance to attrition and osmotic shock

## **SYSTEMS**

Layered Beds

## **TYPICAL PACKAGING**

- 1 ft³ Sack
- 25 L Sack
- 5 ft³ Drum (Fiber)
- 1 m³ Supersack
- 42 ft³ Supersack

# **TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:**

Polymer Structure	Gel polyacrylic crosslinked with divinylbenzene
Appearance	Spherical Beads
Functional Group	Tertiary Amine
Ionic Form	FB form
Total Capacity	1.6 eq/L (35.0 Kgr/ft³) (FB form)
Moisture Retention	56 - 62 % (FB form)
Particle Size Range	300 - 630 μm
< 300 μm (max.)	3 %
Uniformity Coefficient (max.)	1.4
Irreversible Swelling (max.)	5 %
Reversible Swelling, FB → Cl⁻ (max.)	25 %
Specific Gravity	1.08
Shipping Weight (approx.)	665 - 695 g/L (41.6 - 43.4 lb/ft³)
Temperature Limit	40 °C (104.0 °F) (FB form)



The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Purolite expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.



T +1 610 668 9090 F +1 610 668 8139 americas@purolite.com

#### EMEA

T +44 1443 229334 F +44 1443 227073 europe@purolite.com

#### Asia Pacific

T +86 571 876 31382 F +86 571 876 31385 asiapacific@purolite.com

#### FSU

T +7 495 363 5056 F +7 495 564 8121 fsu@purolite.com